

AMENDMENTS TO THE CLAIMS

Claims 1-14 (canceled)

15. (New): Apparatus for releasing a magnetic security device, the apparatus comprising: a first portion for locating an article in a first direction and a second portion for locating an article in a second direction substantially perpendicular to the first direction, the first and second portions forming a slot for receiving the article but physically restraining the article in the first and second directions as it is brought into contact with the first and second portions; at least one of the first and second portions including magnetic release means arranged to assist in locating the article in a third direction substantially perpendicular to the first and second directions by magnetic attraction of the security device as the article is brought into contact with the at least one of the first and second portions so as to align the magnetic security device with the magnetic release means, the magnetic release means being arranged to provide a first magnetic force in the first direction and a second magnetic force in the second direction for releasing a magnetic security device from the article.

16. (New): Apparatus for releasing a magnetic security device, the apparatus comprising: a first portion for locating an article in a first direction and a second portion for locating an article in a second direction substantially perpendicular to the first direction, so as to provide an L-shaped slot or receptacle capable of receiving articles of a wide range of shapes and sizes having a security device installed adjacent two substantially perpendicular sides thereof, at least one of the first and second portions including magnetic release means arranged to provide a first magnetic force in the first direction and a second magnetic force in the second direction for releasing a magnetic security device from the article.

17. (New): Apparatus as claimed in claim 15 in which the first portion defines a first plane and the second portion defines a second plane substantially perpendicular to the first plane.

18. (New): Apparatus as claimed in claim 17 in which the first and second planes define a slot having a substantially L-shaped cross-section.

19. (New): Apparatus as claimed in claim 15 in which the first and second portions respectively comprise a base portion and a top portion upstanding therefrom.

20. (New): Apparatus as claimed in claim 19 in which the first and second portions are connected together by means of at least one mutually engageable projection and recess.

21. (New): Apparatus as claimed in claim 15 in which a first magnet mounted in the first portion provides the magnetic force in direction and a second magnet mounted in the second portion provides the magnetic force in the second direction.

22. (New): Apparatus as claimed in claim 21 in which at least one of the first and second magnet comprises a plurality of parts which are held together in a configuration in which they tend to repel each other.

23. (New): Apparatus as claimed in claim 22 in which at least one of the first and second magnets comprise a central part with a plurality of further parts adjacent thereto, the magnetic axes of each of the further parts being perpendicular to that of the central part.

24. (New): Apparatus as claimed in claim 15 having closure means moveable between an open position which provides access to the magnetic release

means and a closed position which prevents an article being presented to the magnetic release means.

25. (New): Apparatus as claimed in claim 24 in which the closure means comprises a slidable or pivotable cover.

26. (New): Apparatus as claimed in claim 24 having locking means for locking the closure means in the closed position.

27. (New): Apparatus as claimed in claim 16 in which at least one of the first and second portions are arranged to assist in locating the article in a third direction substantially perpendicular to the first and second directions by magnetic attraction of the security device as the article is brought into contact with the first and second portions so as to align the magnetic security device with the magnetic release means.

28. (New): A method of releasing a magnetic security device comprising the steps of providing apparatus as claimed in claim 15 and presenting an article with a magnetic security device thereto to release the magnetic security device therefrom.